



LOS ANGELES AREA (800) 366-3473
 NEW YORK AREA (800) 526-4592
 CHICAGO AREA (800) 547-3473
 ATLANTA AREA (800) 762-0542

Hallmann Sales, LLC
 866-966-9596
 info@hallmann-sales.com

Call Potter Roemer for current listings and approvals. Dimensions are subject to manufacturer's tolerances, and change without notice. We assume no responsibility for use of superseded or void data.



PORTABLE FIRE EXTINGUISHERS



ABC MULTI-PURPOSE DRY CHEMICAL

REGULARLY FURNISHED: Red glossy polyester coated steel cylinder with pressure gauge, wall mounting bracket and hose or nozzle as indicated. Contents stored under pressure at approximately 195 PSI.

✓ Model No.	Size lbs. / kg	U/L Rating	FM Appv'l	Height	Dia.	Range of Stream	Type Discharge
3002	2-1/2 / 1.1	1A:10B:C	Yes	14-3/4"	3"	9'-15'	Nozzle
3005	5 / 2.3	2A:10B:C	Yes	15-1/4"	4-1/4"	12'-18'	Hose
3005-3	5 / 2.3	3A:40B:C	No	15-1/4"	4-1/4"	12'-18'	Hose
3006	6 / 2.7	3A:40B:C	Yes	16"	5"	15'-21'	Hose
3010	10 / 4.5	4A:80B:C	Yes	20"	5"	15'-21'	Hose
3020	20 / 9	20A:120B:C	Yes	23-1/4"	7"	15'-21'	Hose



ABC MULTI-PURPOSE CARTRIDGE OPERATED DRY CHEMICAL

REGULARLY FURNISHED: Red glossy polyester coated steel cylinder with hose, squeeze grip control nozzle and wall mounting bracket. Carbon dioxide gas contained in outside cartridge at approximately 850 PSI (70°F) provides cylinder pressurization and agent discharge upon activation.

✓ Model No.	Size lbs. / kg	U/L Rating	FM Appv'l	Height	Dia.	Overall Width	Range of Stream	Type Discharge
3052	10 / 4.5	4A:60B:C	No	18-1/2"	5-1/4"	9"	18'-22'	Hose
3054	20 / 9	20A:80B:C	No	21-1/2"	6-3/4"	10-3/4"	18'-22'	Hose
3056	25 / 11.3	20A:120B:C	No	26-1/4"	6-3/4"	10-3/4"	18'-22'	Hose



PRESSURIZED WATER/F.F.P. FOAM

REGULARLY FURNISHED: Stainless steel shell with pressure gauge and wall mounting bracket. Shipped empty, to be charged at destination by authorized personnel.

✓ Model No.	Size Gal. / Lt	U/L Rating	FM Appv'l	Height	Dia.	Range of Stream	Type Discharge
3202 (Water)	2-1/2 / 9.4	2A	Yes	24-1/2"	7"	45'-55'	Hose
3252 (Foam)	2-1/2 / 9.4	3A:20B	No	24-1/2"	7"	10'-15'	Hose & Nozzle



BC DRY CHEMICAL

REGULARLY FURNISHED: Red glossy polyester coated steel cylinder with pressure gauge, wall mounting bracket and hose or nozzle as indicated. Contents stored under pressure at approximately 195 PSI.

✓ Model No.	Size lbs. / kg	U/L Rating	FM Appv'l	Height	Dia.	Range of Stream	Type Discharge
3302	2-1/2 / 1.1	10B:C	Yes	14-3/4"	3"	9'-15'	Nozzle
3305	5 / 2.3	10B:C	Yes	15-1/4"	4-1/4"	12'-18'	Nozzle
3305-3	5-1/2 / 2.5	40B:C	No	15-1/4"	4-1/4"	12'-18'	Hose
3306	6 / 2.7	40B:C	Yes	16-3/4"	5"	15'-21'	Hose
3310	10 / 4.5	60B:C	Yes	20"	5"	15'-21'	Hose
3320	20 / 9	120B:C	Yes	23-1/4"	7"	15'-21'	Hose

MEMBERS:



MODEL NUMBER

3002 - 3320