

# Safeguard Series Semi Recessed Fire-Rated Fire Extinguisher Cabinets

**hallmann|sales**

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

**Project:** \_\_\_\_\_

**Specification Reference:** \_\_\_\_\_

**Contractor:** \_\_\_\_\_

**Architect:** \_\_\_\_\_

**Date:** \_\_\_\_\_

Model Number	Trim	Tub Size			Overall Outside Trim Dim.		Rough Opening			Shipping Weight In Lbs.	Extinguisher Size In Lbs.
		W	H	D	W	H	W	H	D		
SSRC-5	1-3/4"	8"	17"	5"	10-3/4"	19-3/4"	9-3/4"	18-9/16"	4"	28	5
SSRC-10	3"	9-1/2"	24"	6"	13-1/2"	28-1/2"	11-1/16"	25-9/16"	3-3/4"	38	10
SSRC-20	4"	12"	27"	8"	16"	31"	13-9/16"	28-9/16"	4-3/4"	54	20

## SAFEGUARD Construction Specifications:

The SAFEGUARD Series offers a full line of fire extinguisher cabinets to accommodate a full range of fire extinguishers. These cabinets are FIRE RATED cabinets.

Our Fully- and Semi-Recessed Fire Extinguisher Cabinets meet with the current Americans with Disabilities Act of 1990 Guidelines.

**Door Panel/Front:** 16 ga. cold-rolled steel.

**Tub:** 22 ga. cold-rolled steel.

**Exterior Tub:** 22 ga. Satin coat galvanized steel completely lined with 5/8" Type X UL gypsum board.

**Hardware:** Full-length piano hinge, Roller ball catch, Four inch solid brass, polished chrome plated pull handle.

**Finish:** Baked white enamel over rust-inhibiting phosphate treated steel.

**Door Style:** Full Glass

**Door Glazing:** DSA glass standard on all cabinets. Clear wire glass, tempered safety glass, 1/8" or 1/4" acrylic panels available as options.

UL Classified 5/8" Type X gypsum board inserted in the cavity between the two layers.

Warnock Hersey has approved the Safeguard Cabinets to be mounted in any face of fire rated steel or wood stud for up to 2 hour rated walls without affecting its fire rating. The above meets the requirement test ASTM-E119-98 with test report WHI-495-1534. MOUNTING INSTRUCTIONS are supplied with each Safeguard cabinet.

