

Acudor Flush Drywall Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____
 Specification Reference: _____
 Contractor: _____
 Architect: _____
 Date: _____

For Walls and Ceilings

Material: 20 gauge galvanized formed door panel, flanged on four sides; 26 gauge galvanized frame, with multiple bends for added strength

Door: Formed door panel, flanged on four sides

Frame: Multiple bends for added strength. Integral perforated tapping bead adds extra rigidity

Hinge: Concealed

Latch: Stainless steel screwdriver operated cam latch. Also available: cylinder lock & key; allen head cam latch; spanner head cam latch

Finish: 5 stage iron phosphate preparation with prime coat of white baked enamel. Frame to be mill finish

Model No.	Door Size W x H	Opening W x H	Latch
DW-5040	6x6	6-3/8x6-3/8	1
DW-5040	8x8	8-3/8x8-3/8	1
DW-5040	10x10	10-3/8x10-3/8	1
DW-5040	12x12	12-3/8x12-3/8	1
DW-5040	14x14	14-3/8x14-3/8	1
DW-5040	16x16	16-3/8x16-3/8	2
DW-5040	18x18	18-3/8x18-3/8	2
DW-5040	22x22	22-3/8x22-3/8	4
DW-5040	24x24	24-3/8x24-3/8	4
DW-5040	24x36	24-3/8x36-3/8	5
DW-5040	30x30	30-3/8x30-3/8	5
DW-5040	36x36	36-3/8x36-3/8	5

OPTIONS: (AT EXTRA COST)

Cylinder Lock

