

Acudor Gasketed Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____
 Specification Reference: _____
 Contractor: _____
 Architect: _____
 Date: _____

For Walls and Ceilings

Material: Stainless Steel or Steel: 16 gauge door, 16 gauge mounting frame.

Door: Flush to frame with reinforced edges.

Frame: Flange to be 1" wide.

Hinge: Concealed.

Gasket: 1/8" x 3/8" closed cell neoprene gasket.

Latch: Stainless steel screwdriver operated cam latch.

Also available: cylinder lock & key, allen head cam latch, spanner head cam latch.

Finish: Stainless steel: #4 satin polish.

Steel: 5 stage iron phosphate with prime coat of white baked enamel.

Model No.	Door Size W x H	Opening W x H	Latch
AS-9000	12x12	12-3/8x12-3/8	1
AS-9000	18x18	18-3/8x18-3/8	2
AS-9000	24x24	24-3/8x24-3/8	4
AS-9000	24x36	24-3/8x36-3/8	5
AS-9000-SS	12x12	12-3/8x12-3/8	1
AS-9000-SS	18x18	18-3/8x18-3/8	2
AS-9000-SS	24x24	24-3/8x24-3/8	4
AS-9000-SS	24x36	24-3/8x36-3/8	5

OPTIONS: (AT EXTRA COST)

Cylinder Lock

