

# Acudor Universal Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: \_\_\_\_\_

Specification Reference: \_\_\_\_\_

Contractor: \_\_\_\_\_

Architect: \_\_\_\_\_

Date: \_\_\_\_\_

For Walls and Ceilings

**Material:** 14 gauge door, 14 gauge mounting frame.

**Door:** Flush to frame — rounded safety corners.

**Frame:** One piece outer flange welded to mounting frame.

**Hinge:** Continuous, concealed.

**Latch:** Stainless steel screwdriver operated cam latch.

**Finish:** Steel: 5 stage iron phosphate preparation with prime coat of white baked enamel.

**OPTIONS: (AT EXTRA COST)**

Cylinder Lock

Allen Head Cam Latch with Security Pin



Model No.	Door Size W x H	Wall Opening W x H	Latch
UF-5000	6x6	6-3/8x6-3/8	1
UF-5000	8x8	8-3/8x8-3/8	1
UF-5000	8x12	8-3/8x12-3/8	1
UF-5000	10x10	10-3/8x10-3/8	1
UF-5000	12x12	12-3/8x12-3/8	1
UF-5000	12x16	12-3/8x16-3/8	2
UF-5000	12x18	12-3/8x18-3/8	2
UF-5000	12x24	12-3/8x24-3/8	2
UF-5000	14x14	14-3/8x14-3/8	1
UF-5000	16x16	16-3/8x16-3/8	2
UF-5000	16x24	16-3/8x24-3/8	2
UF-5000	18x18	18-3/8x18-3/8	2
UF-5000	18x24	18-3/8x24-3/8	2
UF-5000	22x22	22-3/8x22-3/8	4
UF-5000	22x30	22-3/8x30-3/8	5
UF-5000	22x36	22-3/8x36-3/8	5
UF-5000	24x24	24-3/8x24-3/8	4
UF-5000	24x30	24-3/8x30-3/8	5
UF-5000	24x36	24-3/8x36-3/8	5
UF-5000	24x48	24-3/8x48-3/8	5
UF-5000	30x30	30-3/8x30-3/8	5
UF-5000	36x36	36-3/8x36-3/8	5

