

Acudor Universal Flush Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____

Specification Reference: _____

Contractor: _____

Architect: _____

Date: _____

Model No.	Door Size W x H	Opening W x H	Latch
ED-2002	6x6	6-3/8x6-3/8	1
ED-2002	8x8	8-3/8x8-3/8	1
ED-2002	10x10	10-3/8x10-3/8	1
ED-2002	12x12	12-3/8x12-3/8	1
ED-2002	14x14	14-3/8x14-3/8	1
ED-2002	16x16	16-3/8x16-3/8	1
ED-2002	18x18	18-3/8x18-3/8	1
ED-2002	20x20	20-3/8x20-3/8	1
ED-2002	24x24	24-3/8x24-3/8	1
ED-2002	24x36	24-3/8x36-3/8	2

For Walls and Ceilings

Material: 18 gauge steel door and frame

Door: Flush to frame, formed edges.

Frame: 1" wide outside flange by 1 1/2" deep (2.5 x 3.8cm) mounting frame with holes

Hinge: Concealed.

Latch: Stainless steel screwdriver operated cam latch.

Finish: White alkyd baking enamel

OPTIONS: (AT EXTRA COST)

Cylinder Lock

