

WB Exterior Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____
 Specification Reference: _____
 Contractor: _____
 Architect: _____
 Date: _____

For Walls Only

Door: 16 ga. steel, trim 1-1/2" wide

Frame: 16 ga. steel, 2-3/8" depth

Insulation: Double layer of 1" GreenGuard® Extruded Polystyrene insulation board, with R-Value of 10 @ 75°F Mean (5.0 x 2, FM approved)

Gasketing: Open celled microcellular polyurethane on inside of door. Closed cell neoprene sponge SC42 W/PSA stripping gasketing on the back of the door

Hinge: Continuous piano hinge allows opening to 180°

Latches: Chrome plated "T" type handle with pivot rod 3 point catch. WB 151 key code cylinder lock. Opens from the outside only

Finish: Zinc dipped baked grey enamel

Application: For exterior purposes, weather resistant

Due to Engineering considerations, special sizes are not available

Model No.	Door Size W x H	Wall Opening W x H
EXT 1300	12x12	12 1/4 x 12 1/4
EXT 1300	14x14	14 1/4 x 14 1/4
EXT 1300	16x16	16 1/4 x 16 1/4
EXT 1300	18x18	18 1/4 x 18 1/4
EXT 1300	22x30	22 1/4 x 30 1/4
EXT 1300	22x36	22 1/4 x 36 1/4
EXT 1300	24x24	24 1/4 x 24 1/4
EXT 1300	24x36	24 1/4 x 36 1/4
EXT 1300	30x36	30 1/4 x 36 1/4
EXT 1300	36x36	36 1/4 x 36 1/4

