

# Karp Flush Drywall Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: \_\_\_\_\_

Specification Reference: \_\_\_\_\_

Contractor: \_\_\_\_\_

Architect: \_\_\_\_\_

Date: \_\_\_\_\_

The KDW has a textured frame and bead so drywall joint compound can be applied in sufficient thickness to conceal flange. Pre-punched holes in the flange facilitate fastening the flange to framing members with drywall screws.

For Walls and Ceilings

For Drywall Only

**Frame:** 16 gauge steel.

**Door:** 14 gauge steel.

**Trim:** Galvanized drywall bead.

**Hinge:** Concealed continuous piano hinge.

**Finish:** Prime coat of rust inhibitive electrostatic powder, baked grey enamel.

Model No.	Door Size H x W	Opening H x W	Stud Catches / Latches
KDW	6X6	6 3/8X6 3/8	1
KDW	8X8	8 3/8X8 3/8	1
KDW	10X10	10 3/8X10 3/8	1
KDW	12X12	12 3/8X12 3/8	1
KDW	14X14	14 3/8X14 3/8	2
KDW	16X16	16 3/8X16 3/8	2
KDW	18X18	18 3/8X18 3/8	2
KDW	22X22	22 3/8X22 3/8	4
KDW	24X24	24 3/8X24 3/8	5
KDW	36X24	36 3/8X24 3/8	5

**OPTIONS:** (AT EXTRA COST)

Cylinder Lock

