

WB Drywall Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____
 Specification Reference: _____
 Contractor: _____
 Architect: _____
 Date: _____

Door: 14 ga. steel

Frame: 16 ga. steel. These models have a 1" wide perforated flange of 24 ga. galvanized steel for mounting purposes

Hinge: Full length piano hinge on 6 x 6 and 8 x 8. Full length piano hinge also on 24 x 36 and larger. Concealed hinge on sizes 10 x 10 to 24 x 24

Latches: Flush, stainless steel cam latch

Finish: Grey baked enamel coat

Model No.	Door Size W x H	Wall Opening W x H	Cam Latch
DW 400	8x8	8 1/4 x 8 1/4	1
DW 400	10x10	10 1/4 x 10 1/4	1
DW 400	12x12	12 1/4 x 12 1/4	1
DW 400	14x14	14 1/4 x 14 1/4	3
DW 400	16x16	16 1/4 x 16 1/4	3
DW 400	18x18	18 1/4 x 18 1/4	3
DW 400	22x22	22 1/4 x 22 1/4	4
DW 400	22x30	22 1/4 x 30 1/4	4
DW 400	24x24	24 1/4 x 24 1/4	4

OPTIONS: (AT EXTRA COST)

- Stainless Steel Type 304
- Stainless Steel Type 316 No. 4 Satin Finish Brushed
- Stainless Steel Type 316 No. 4 Satin Finish Non-Brushed

Options:

- WB 151 Key Code Cylinder locks-keyed alike with 2 keys per lock
- Mortise Best Lock (or locks supplied by others)
- Weather resistive neoprene gasketing all 4 sides*
- Special sizes available

* Closed cell sponge, blend of Neoprene/EPDM/SBR. Meets ASTM D-1056: SCE 41, RE 41, 2A1; substrate UL 94HF-1 recognized.

