

WB True Fit Duct Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Frame: Die formed 22 ga. flanged frame. Die formed 24 ga. door

Door: 22 ga. steel. Double wall construction.

Hinge: Continuous hinge.

Finish: Mill finish.

Gasketing: Polyester open celled foam.

Insulation: 1" fiberglass insulation.

This convenient, economical access door is easy to install with notched edges, to provide for a quick and simple installation. Doors are available in either hinged or double cam construction (item is union labeled).



Project: _____
 Specification Reference: _____
 Contractor: _____
 Architect: _____
 Date: _____

Model No.	Door Size W x H	Frame Neck O.D. W x H
ADH 1400	6 x 6	4 7/8 x 4 7/8
ADH 1400	8 x 8	6 7/8 x 6 7/8
ADH 1400	10 x 10	8 7/8 x 8 7/8
ADH 1400	12 x 12	10 7/8 x 10 7/8
ADH 1400	14 x 14	12 7/8 x 12 7/8
ADH 1400	16 x 16	14 7/8 x 14 7/8
ADH 1400	18 x 18	16 7/8 x 16 7/8
ADH 1400	24 x 24	22 7/8 x 22 7/8

