

WB General Purpose Premium Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____
 Specification Reference: _____
 Contractor: _____
 Architect: _____
 Date: _____

SPECIFICATIONS:

Door: 14 ga. steel. Trim is 1-1/2" wide
 Frame: 18 ga. steel having a depth of 1-3/4"
 Hinges: Fully-concealed hinge up to and including 24 x 24.
 Allows opening to 165°, Over 24 x 24 is semi-concealed allowing 180°
 Latches: Flush, stainless steel cam latch
 Finish: Grey baked enamel coat



OPTIONS: (AT EXTRA COST)

Finishes:

- Stainless Steel Type 304
- Stainless Steel Type 316 No. 4 Satin
- Stainless Steel Type 316 No. 4 Satin

Options:

- WB 151 Key Code Cylinder locks-keyed alike with 2 keys per lock
- Mortise Best Lock (or locks supplied by others)
- Weather resistive neoprene gasketing all 4 sides*
- Special sizes available

* Closed cell sponge, blend of Neoprene/EPDM/SBR. Meets ASTM D-1056: SCE 41, RE 41, 2A1; substrate UL 94HF-1 recognized.

Model No.	Door Size W x H	Wall Opening W x H	Cam Latch
GP 100	6x6	6 1/4 x 6 1/4	1
GP 100	8x8	8 1/4 x 8 1/4	1
GP 100	8x12	8 1/4 x 12 1/4	1
GP 100	10x10	10 1/4 x 10 1/4	3
GP 100	12x12	12 1/4 x 12 1/4	3
GP 100	14x14	14 1/4 x 14 1/4	3
GP 100	16x16	16 1/4 x 16 1/4	3
GP 100	18x18	18 1/4 x 18 1/4	3
GP 100	18x24	18 1/4 x 24 1/4	4
GP 100	22x22	22 1/4 x 22 1/4	4
GP 100	22x30	22 1/4 x 30 1/4	4
GP 100	24x24	24 1/4 x 24 1/4	4
GP 100	24x30	24 1/4 x 30 1/4	4
GP 100	24x36	24 1/4 x 36 1/4	5
GP 100	24x48	24 1/4 x 48 1/4	6
GP 100	30x30	30 1/4 x 30 1/4	6
GP 100	36x36	36 1/4 x 36 1/4	7
GP 100	36x48	36 1/4 x 48 1/4	8
GP 100	48x48	48 1/4 x 48 1/4	12

