

WB Removable Panel Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____

Specification Reference: _____

Contractor: _____

Architect: _____

Date: _____

Door: 14 ga. steel. Trim being 1-1/2" wide.

Frame: 18 ga. steel having a depth of 1-3/4"

Latches: Flush, stainless steel cam latches on all 4 sides

Finish: Grey baked enamel coat

Model No.	Door Size W x H	Wall Opening W x H	Cam Latch
RP 110	8x8	8 1/4 x 8 1/4	4
RP 110	12x12	12 1/4 x 12 1/4	4
RP 110	18x18	18 1/4 x 18 1/4	4
RP 110	24x24	24 1/4 x 24 1/4	8



OPTIONS: (AT EXTRA COST)

Finishes:

- Stainless Steel Type 304
- Stainless Steel Type 316 No. 4 Satin Finish Brushed
- Stainless Steel Type 316 No. 4 Satin Finish Non-Brushed

Options:

- WB 151 Key Code Cylinder locks-keyed alike with 2 keys per lock
- Mortise Best Lock (or locks supplied by others)
- Weather resistive neoprene gasketing all 4 sides*
- Special sizes available

* Closed cell sponge, blend of Neoprene/EPDM/SBR. Meets ASTM D-1056: SCE 41, RE 41, 2A1; substrate UL 94HF-1 recognized.

