

# WB Utility Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: \_\_\_\_\_

Specification Reference: \_\_\_\_\_

Contractor: \_\_\_\_\_

Architect: \_\_\_\_\_

Date: \_\_\_\_\_

**Door:** 16 ga. steel. Trim being 1-1/2" wide

**Frame:** 16 ga. steel having a depth of 1-3/4"

**Hinge:** Full length semi-concealed piano hinge

**Latches:** Flush, stainless steel cam latch

**Finish:** Grey baked enamel coat



Model No.	Door Size W x H	Wall Opening W x H	Cam Latch
UAD 200	6x6	6 1/8 x 6 1/8	1
UAD 200	8x8	8 1/8 x 8 1/8	1
UAD 200	10x10	10 1/8 x 10 1/8	1
UAD 200	12x12	12 1/8 x 12 1/8	1
UAD 200	14x14	14 1/8 x 14 1/8	3
UAD 200	16x16	16 1/8 x 16 1/8	3
UAD 200	18x18	18 1/8 x 18 1/8	3
UAD 200	22x22	22 1/8 x 22 1/8	4
UAD 200	22x30	22 1/8 x 30 1/8	5
UAD 200	24x24	24 1/8 x 24 1/8	4
UAD 200	24x30	24 1/8 x 30 1/8	5
UAD 200	24x36	24 1/8 x 36 1/8	5
UAD 200	24x48	24 1/8 x 48 1/8	6
UAD 200	30x30	30 1/8 x 30 1/8	6
UAD 200	36x36	36 1/8 x 36 1/8	9

**OPTIONS:** (AT EXTRA COST)

**Finishes:**

- Stainless Steel Type 304
- Stainless Steel Type 316 No. 4 Satin Finish Brushed
- Stainless Steel Type 316 No. 4 Satin Finish Non-Brushed

**Options:**

- WB 151 Key Code Cylinder locks-keyed alike with 2 keys per lock
- Mortise Best Lock (or locks supplied by others)
- Weather resistive neoprene gasketing all 3 sides\*
- Special sizes available

\* Closed cell sponge, blend of Neoprene/EPDM/SBR. Meets ASTM D-1056: SCE 41, RE 41, 2A1; substrate UL 94HF-1 recognized.

