

# Buckeye ABC Dry Chemical Fire Extinguisher



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project:	_____
Specification Reference:	_____
Contractor:	_____
Architect:	_____
Date:	_____

- **IDEAL USES:** Homes, office buildings, warehouses, farms and woodworking areas.  
(NOTE - Not recommended for use on expensive delicate equipment or computers.)
- Monoammonium Phosphate based dry chemical agent.
- Rated for use on "A", "B", and "C" class fires. Provides the widest, most practical range of fire protection.
- Rechargeable
- Steel cylinders with a baked-on polyester enamel coating stand up to harsh environments.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 Standards.



Size/Model	2.5 ABC V/B	5 ABC	5 ABC V/B	10 ABC TALL	20 ABC
Part No. Alum Valve	B2.5ABC	B5ABC	B5ABCVB	B10ABC	B20ABC
Capacity lbs/kg	2.5 / 1.13	5 / 2.27	5 / 2.27	10 / 4.54	20 / 9.07
U.L. Rating	1A: 10B:C	3A: 40B:C	3A: 40B:C	4A: 80B:C	20A: 120B:C
Ship Wt. Alum Valve	5.5 / 2.49	9.5 / 4.3	9.75 / 4.4	17.25 / 8.1	33 / 15.0
Height ( in / cm )	14.75 / 37.5	16.375 / 41.6	16.375 / 41.6	21 / 53.3	21.25 / 53.8
Width ( in / cm )	4.875 / 12.4	7.25 / 18.4	7.25 / 18.4	7.75 / 19.7	8.25 / 22.2
Diameter ( in / cm )	3.375 / 8.6	4.25 / 10.8	4.25 / 10.8	5.125 / 13.0	7.5 / 19.1
Bracket	Veh / Marine	Wall	Veh / Mar	Wall	Wall
Range ( Feet/Meters )	9-15/2.7-4.6	12-18/3.7-5.5	12-18/3.7-5.5	15-21/4.6-6.4	15-21/4.6-6.4
Discharge Times sec.	9	14	14	22	26
Operating Pressure	100PSI / 690 kPa	195PSI / 1340 kPa	195PSI / 1340 kPa	195PSI / 1340 kPa	195PSI / 1340 kPa
Cylinder	Steel	Steel	Steel	Steel	Steel