STI Beam Smoke Damage Stopper®



STI-9706

FEATURES

- Super tough construction of 9-gauge coated steel wire makes guards extremely difficult to break.
- · Coated with a tough, corrosion resistant polyester shell.
- Protection against misalignment and false fire alarms.
- \cdot Five sizes to choose from.
- Designed to protect both transmitter and receiver units (sold individually).
- \cdot Fast and easy installation.
- \cdot May be painted once prior to installation.
- · Lifetime guarantee against breakage in normal use.



For more information, call 1-800-888-4784 (4STI) or visit www.sti-usa.com

PRODUCT OVERVIEW

Five models are offered to protect the vital sensor units of projected beam type smoke detectors in large areas (such as gymnasiums, warehouses and auditoriums). STI Beam Smoke Damage Stoppers are designed to protect both transmitter and receiver sensors. Installation is simple with anchors and screws provided.

BACKED BY A LIFETIME GUARANTEE

As all STI protective covers, Beam Smoke Damage Stoppers are backed by a lifetime guarantee against breakage in normal use. They are constructed of 9-gauge, welded steel wire coated with a tough, corrosion resistant polyester shell.

STI Beam Smoke Damage Stopper[®]

Dimensions and Technical Information

MODELS AVAILABLE


STI-9624 Beam Smoke Damage Stopper for Fireray 50/100 R STI-9625 Beam Smoke Damage Stopper for System Sensor Beam Smoke Detector 6424

STI-9706	Beam Smoke Damage Stopper - flush mount for System			
	Sensor 1224			
STI-9707	Beam Smoke Damage Stopper - surface mount			

Tamper resistant stainless steel screws, #8 x 1 1/2 in. **SUB-82** snake eye


19038 5/16 in. hex drive tamper bit for tamper resistant screws


MODEL	HEIGHT	WIDTH	DEPTH				
<u>STI-9623</u>	7.75 in. (196mm)	6 in. (152mm)	6 in. (152mm)				
<u>STI-9624</u>	8.875 in. (225mm)	5.5 in. (140mm)	4.75 in. (120mm)				
<u>STI-9625</u>	7.875 in. (200mm)	10.25 in. (260mm)	12.625 in. (321mm)				
<u>STI-9706</u>	10.82 in. (275mm)	9.32 in. (237mm)	4 in. (120mm)				
<u>STI-9707</u>	11 in. (280mm)	9.62 in. (244mm)	5.5 in. (140mm)				
NOTE: No tamper resistant stainless steel screws available for STI-9625.							



STI-9623

STI-9624





8.875 in.

(225mm)

APPROVALS AND WARRANTY

TESTING

STI-9625 has been tested and approved or listed by: · UL. cUL Listed S3504

WARRANTY

Lifetime guarantee against breakage in normal use.

		9.32 in. (237mm)							
r L						Ñ			
			•	\neg					
				1					
	_ c	EN	TEF	٢.					
	ì	ŪTO	DU	τ					
			ł						




5.50 in. (140mm)

4 in. (102mm)

11 in. 280mm) 10.32 in

(262mm)



STI-9706



Safety Technology International, Inc. 2306 Airport Road Waterford, Michigan 48327, USA

Tel: 248-673-9898 Fax: 248-673-1246 Tollfree: 800-888-4784 info@sti-usa.com www.sti-usa.com

Unit 49G Pipers Road Park Farm Industrial Estate Redditch, Worcestershire B98 OHU England

Tel: 44 (0) 1527 520 999 Fax: 44 (0) 1527 501 999 Free: 0800 085 1678 (UK) www.sti-europe.com