STI STEEL WEB STOPPERS[®]

UL Listed Protectors for Areas Where Abuse to Smoke Detectors is Severe

STI borrowed from nature's master builder, the spider, to create a web of protection from vandalism and accidental damage with these UL Listed wire guards. They are constructed of 9-gauge steel wire with corrosion resistant polyester coating or 9-gauge stainless steel wire. Together, they cover virtually every smoke detector model available today.

Backed by a lifetime guarantee

As all STI protective covers, these Steel Web Stoppers are backed by a lifetime guarantee against breakage in normal use. Installation and servicing are easy with models for both flush and surface mounting. Highly recommended for areas where abuse to smoke detectors is severe.

- Patented (D368,670) web-like octagon shape of 9-gauge coated steel wire makes them extremely difficult to break.
- Models to fit virtually all smoke detectors available today.
- Steel Web Stoppers have corrosion resistant polyester coating (stainless steel models have no coating).
- UL Listed to U.S. safety standards (S3504) for any UL Listed detector, does not require any sensitivity adjustment (see reverse for details).
- UL Listing for STI-9713 (S3504) with detectors listed on reverse.

Safety Technology International, Inc.

vith detectors match decor.

2306 Airport Road • Waterford, Michigan 48327-1209 Phone: 248-673-9898 • Fax: 248-673-1246 • Toll Free: 800-888-4784 • E-mail: info@sti-usa.com • Web: www.sti-usa.com

Europe Branch Office • Unit 49G Pipers Road • Park Farm Industrial Estate • Redditch • Worcestershire • B98 0HU • England Tel: 44 (0) 1527 520 999 • Fax: 44 (0) 1527 501 999 • Freephone: 0800 085 1678 (UK only) • E-mail: info@sti-europe.com • Web: www.sti-europe.com

• Tamper resistant hardware is available.

- CSFM (7300-1416:100) Approved (9600 Series only).
- Lifetime guarantee against breakage in normal use.
- Stainless steel versions available for flush mount or surface mount.
- Fast and easy installation.
- Simple removal for servicing detector.
- May be spray painted once prior to installation to match decor.







Features

STI STEEL WEB STOPPERS Dimensions and Technical Information

Festing Approvals

Notice

STI-9601	Steel Web Stopper, Low Profile - Flush Mount
STI-9601-SS	Steel Web Stopper, Low Profile - Flush Mount - Stainless Steel
STI-9602	Steel Web Stopper, Low Profile - Surface Mount
STI-9604	Steel Web Stopper for Mini Smoke Detectors - Flush Mount
STI-9604-SS	Steel Web Stopper for Mini Smoke Detectors - Flush Mount - Stainless Steel
STI-9605	Steel Web Stopper for Mini Smoke Detectors - Surface Mount
STI-9605-SS	Steel Web Stopper for Mini Smoke Detectors - Surface Mount - Stainless Steel
STI-9609	Steel Web Stopper, High Profile - Flush Mount
STI-9609-SS	Steel Web Stopper, High Profile - Flush Mount - Stainless Steel
STI-9610	Steel Web Stopper, High Profile - Surface Mount
STI-9712	Steel Web Stopper for Photoelectric Smoke Detector - Surface Mount (Not UL Tested)
STI-9713	Steel Web Stopper for Photoelectric Smoke Detector - Flush Mount
SUB-82	Tamper resistant stainless steel screws, #8 X 1 1/2 in. snake eye (quantity 4)
19038	Spanner bit for tamper resistant screws with 5/16 in. hex drive
STI-8170	Polycarbonate mounting backplate for flush and surface mount models. Recommended for irregular and unstable mounting surfaces such as drop ceilings

It has been tested and/or listed by:

STI-9601 - STI-9610 Series UL Listing

- Underwriter Laboratories No. S3504 for any UL Listed detector, does not require any sensitivity adjustment
- California State Fire Marshal No. 7300-1416:100
- MEA approved #49-00-E


STI-9713 UL Listing


• Underwriter Laboratories No. S3504 for specific detectors listed below (manufactured after June 1, 2004):


ADT 2951ADT, EST 2251FB, FCI ASD-PL2, Fire-Lite SD355, Gamewell SS-P, Honeywell TC806B1076, JCI 2951J, Mircom MIX-2251B, Notifier FSP-851, Secutron MRI-2251B, System Sensor 2251B


STI also offers other models of Steel Web Stoppers to cover smoke beam detectors, PIRs, bells, clocks, exit signs and similar devices. For additional information, please contact your distributor or Safety Technology International.

Internal Dimensions










8.25 in.(210mm) 8.25 in.(210mm) 2.75 in.(70mm) 5 in.(127mm) → STI-9601

and beams





3.25 in.(83mm)

STI-9604 STI-9604-SS

7 in.(178mm)

