

Acudor Fire Rated Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____

Specification Reference: _____

Contractor: _____

Architect: _____

Date: _____

For Walls

Material: Stainless Steel: 16 gauge door, 16 gauge mounting frame.

Door: Flush to frame with reinforced edges.

Frame: Flange to be 1" wide, mounting frame to have anchor straps.

Hinge: Concealed

Fire Rating: UL — 1-1/2 hour "B" label. ULC — 2 hour "B" label. (optional)

Latch: Universal self-latching bolt, operated by either a knurled knob or flush key.

When master keying is required, doors can be prepared for rim or mortise cylinder locks.

Finish: Type 304 - #4 satin polish.

Model No.	Door Size W x H	Opening W x H	Latch
FB-5060-SS	8x8	8-3/8x8-3/8	1
FB-5060-SS	12x12	12-3/8x12-3/8	1
FB-5060-SS	16x16	16-3/8x16-3/8	1
FB-5060-SS	18x18	18-3/8x18-3/8	1
FB-5060-SS	24x24	24-3/8x24-3/8	1
FB-5060-SS	24x36	24-3/8x36-3/8	2

OPTIONS: (AT EXTRA COST)

Rim Cylinder Lock

Galvanized Steel Drywall Bead Flange

