

## FF Systems – F 2 Access Panel Substitution Request

Please call FF Systems with any questions: (888) 978-1808



**Bauco Model #: Bauco-plus II**

**Frame:**

Aluminum frame, punched/stamped, not welded  
Door frame is recessed for either 1/2" or 5/8" drywall (needs to be specified)

**Board Inlay:**

Moisture and mold resistant gypsum board, screwed

**Latching / locking devices:**

Concealed touch latch (standard)  
Options: Screw cam latch, keyed cylinder lock, torx head cam latch

**Other features:**

Completely removable doors with safety cables, Perimeter gasket  
Virtually invisible access opening (only 1/16" reveal between outer frame and door hatch)

**Installation:**

Wall or ceiling  
New construction or repairs  
Direct in drywall

**Sizes:**

Standard sizes and custom sizes, multi doors



**FF Systems Model #: F2**

**Frame:**

Precision welded, corrosion resistant Aluminum frame - ensures a sturdy frame and consistent gaps / joints when being installed.  
Door frame is recessed for either 1/2" or 5/8" drywall (needs to be specified)

**Board Inlay:**

1/2" or 5/8" moisture and mildew resistant green board / gypsum board, glued in panels up to 24" x 24" (no screw heads in drywall to finish)

**Latching / locking devices:**

Concealed touch latch (standard)  
Options: Screw cam latch, keyed cylinder lock, hex head cylinder lock, pinned hex head lock, mortise prep

**Other features:**

Completely removable doors with safety cables, Perimeter gasket  
Virtually invisible access opening (only 1/16" reveal between outer frame and door hatch)

**Installation:**

Wall or ceiling  
New construction or repairs  
Direct in drywall (MFR preferred / recommended) or on studs / joists

**Sizes:**

Standard sizes and custom sizes, multi doors



**FOR MORE INFORMATION CALL 1-888-926-1365**  
 Superior Specialty Supply • 9 Council Drive • PO Box 417 • Woodsboro, MD 21798 • [www.sssupply.com](http://www.sssupply.com)