

# Wind-Lock Stealth Hinged Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: \_\_\_\_\_  
 Specification Reference: \_\_\_\_\_  
 Contractor: \_\_\_\_\_  
 Architect: \_\_\_\_\_  
 Date: \_\_\_\_\_

Stealth Hinged Access Panels are glass fiber reinforced gypsum (GFRG) panels designed to blend seamlessly into drywall. Designed for both wall and ceiling applications, the hinged Stealth Panel can be used where a locked door is needed but style must still be maintained. The hinged panel is great for use in ceiling applications where there is no space to push a door up, and in wall applications when access to plumbing and electrical is needed

Model No.	Door Size H x W	Opening H x W
TRHAP-9X9	9X9	15X15
TRHAP-12X12	12X12	18X18
TRHAP-16X16	16X16	22X22
TRHAP-18X18	18X18	24X24
TRHAP-24X24	24X24	30X30

- For Walls and Ceilings
- For Drywall
- Tapered edge for tape joint
- Easily textured
- Lightweight
- Blends seamlessly into surrounding drywall
- No shrinking, cracking or rusting
- Single trade installation
- Pre-spotted fastener holes
- Reduce labor costs
- Concealed hinge
- Flush keyed cam lock
- The 9"x9" and 12"x12" feature an innovative Soss hinge
- Shell Thickness 1/8" to 3/16"
- Fastener Test Pull Out (wood stud) 525 lb avg.
- Fastener Test Pull Out (metal stud) 215 lb avg.
- Fastener Push Through Test 350 lb avg.
- Fuel Contribution (ASTM E84-80) 0
- Flame Spread (ASTM E84-80) 0
- Smoke Index (ASTM E84-80) 0
- Combustion (ASTM E84-80) Non-combustible
- Class A Non-Rated —
- CSI Code CSI #083113

