

Wind-Lock Stealth Round Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____
 Specification Reference: _____
 Contractor: _____
 Architect: _____
 Date: _____

The innovative, new round Stealth Access Panel by Wind-lock® is made of GFRG (glass fiber reinforced gypsum). They are designed to blend seamlessly into a drywall ceiling when circular light fixtures, speakers or smoke detectors are being used to maintain the aesthetic theme in the design.

Model No.	Door Size Diameter	Opening H x W
TRRAP-12	12	18X18
TRRAP-16	16	22X22
TRRAP-18	18	24X24
TRRAP-24	24	30X30

- For Ceilings Only
- For Drywall
- Tapered edge for tape joint
- Easily textured
- Lightweight
- Blends seamlessly into surrounding drywall
- No shrinking, cracking or rusting
- Single trade installation
- Pre-spotted fastener holes
- Reduce labor costs
- Shell Thickness 1/8" to 3/16"
- Fastener Test Pull Out (wood stud) 525 lb avg.
- Fastener Test Pull Out (metal stud) 215 lb avg.
- Fastener Push Through Test 350 lb avg.
- Fuel Contribution (ASTM E84-80) 0
- Flame Spread (ASTM E84-80) 0
- Smoke Index (ASTM E84-80) 0
- Combustion (ASTM E84-80) Non-combustible
- Class A Non-Rated —
- CSI Code CSI #083113

