

Acudor Universal Access Doors



Hallmann Sales, LLC

866-966-9596

info@hallmann-sales.com

www.Hallmann-Sales.com

Project: _____

Specification Reference: _____

Contractor: _____

Architect: _____

Date: _____

For Walls and Ceilings

Material: 16" x 16" and smaller: 16 gauge door, 18 gauge mounting frame.

Over 16" x 16": 14 gauge door, 16 gauge mounting frame.

Door: Flush to frame — rounded safety corners.

Frame: One piece outer flange welded to mounting frame.

Hinge: Continuous, concealed.

Latch: Stainless steel screwdriver operated cam latch.

Finish: Steel: Type 304 - #4 satin polish

Model No.	Door Size W x H	Opening W x H	Latch
UF-5000-SS	8x8	8-3/8x8-3/8	1
UF-5000-SS	10x10	10-3/8x10-3/8	1
UF-5000-SS	12x12	12-3/8x12-3/8	1
UF-5000-SS	14x14	14-3/8x14-3/8	1
UF-5000-SS	16x16	16-3/8x16-3/8	2
UF-5000-SS	18x18	18-3/8x18-3/8	2
UF-5000-SS	24x24	24-3/8x24-3/8	4
UF-5000-SS	24x36	24-3/8x36-3/8	5

OPTIONS: (AT EXTRA COST)
Cylinder Lock

