



THIS DOCUMENT IS THE PROPERTY OF ACUDOR PRODUCTS, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF ACUDOR PRODUCTS, INC.

| |
|--|
| INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M BREAK ALL SHARP CORNERS & EDGES TO 0.01 |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: FRACTIONAL 1/16 = ± 1/32 1/32 = ± 1/64 |

COPYRIGHT © 2013
ALL RIGHTS RESERVED

| | |
|---------------------------------|------------------------|
| ACUDOR PRODUCTS | |
| HATCH AW-APS (W) X (H) ALUMINUM | |
| DWG. BY: ICF | SCALE: 1=12 |
| CHK. BY: [blank] | DWG.#/GENERIC - AN-APS |
| SHEET B | QUOTA# |
| SHEET 1 OF 1 | DATE: 10/28/13 |
| REV: | |

- NOTES:**
- 1- MATERIAL: ALUMINUM
 - 2- LOADING: 1560 LBS. PER SQ. FT. (CAPABLE OF HOLDING UP TO 25 FEET HEAD OF WATER)
 - 3- 316 STAINLESS STEEL BOLTS & NUTS
 - 4- AREA OF FRAME IN CONTACT WITH CONCRETE TO BE PAINTED WITH BITUMINOUS COATING