

# Great Stuff Pro Gaps & Cracks Fireblock Sealant

## PRODUCT DESCRIPTION

Great Stuff Pro Gaps & Cracks is a onecomponent, multipurpose, low-expansion construction filler and fireblock sealant.

# APPLICATIONS

Filling, sealing and insulating of joints, voids, and cavities. Also approved for use as an alternative fireblocking material in indoor and outdoor-to-indoor plumbing, HVAC, gas and electrical penetrations.

#### INSTALLATION

Read all instructions and safety information (MSDS) before using any product. Foam bonds to skin quickly — wear gloves, eye protection and work clothes during application. Use drop cloths.

Surface Preparation: Surface should be free of oil, grease and excess moisture.

Application: Great Stuff Pro is applied with a gun applicator at the junction of the plate line and the slab or foundation, any penetration through the top or the bottom of the plate line, cracks and holes in the exterior sheathing from penetration made for utility services, corner and T-wall intersections, and any other place where air might penetrate the exterior envelope.

Storage: Store in cool dry area in upright position.

Limitations: Great Stuff Pro professional foam should not be left permanently exposed to ultraviolet light.

# DOW GREAT STUFF PRO TECHNICAL DATA

Property	Test Method	Gaps & Cracks
Basis		MDI monomer, polyurethane resin propane/isobutene
Characteristics	-	Semí-Rigid
UL Classified (Class 1)	ASTM E-84	Flame Spread 20/Smoke Developed 20
Color		Orange
Density	ASTM D-1622	1.06
Thermal Resistance (R Value)	ASTM C-518	4
Percent Closed Cell Content	ASTM D-2856	>61.63
Application Temperature	·	25°F to 90°F
Storage Temperature	_	Up to 120°F
Service Temperature	_	-200°F to +200°F
Shelf Life	( <del></del>	12 months
Tack Free Time	-	6–7 minutes
Cure time		1 hour
Cutting time		30 minutes
Yield 24 oz can	Bead Size	Linear Feet
	3/8*	1000

## ORDERING INFORMATION

# **Great Stuff Pro—Gaps & Cracks**

PART CODE: W-GSGCFB (Case of 12 cans, Gun Foam)
W-GSTGCFB (Case of 12 cans, Straw Foam)



Approved for use as an alternative fireblocking material by the International Code Council (ICC) per National Evaluation Report No. NER-645.

Halmann Sales, LLC 866-966-9596 www.Hallmann-Sales.com