



**NOTES:**

- 1- MATERIAL: ALUMINUM
- 2- MAXIMUM SPACING BETWEEN SUPPORT: 48"
- 3- APPROX. LADDER WEIGHT: 30 LBS.
- 4- MAX. LENGTH TO SHIP IN ONE PC: 12' LG.
- 5- LADDER CONFORMS TO OSHA STANDARDS 29CFR-1910.27
- 6- LOADING: 300 LBS. AT MIDSPAN

THIS DOCUMENT IS THE PROPERTY OF ACUDOR PRODUCTS, INC AND CONTAINS PROPRIETARY INFORMATION. IT SHALL NOT BE COPIED, FURNISHED NOR DISTRIBUTED (IN WHOLE OR IN PART) WITHOUT PROPER AUTHORIZATION OF ACUDOR PRODUCTS, INC.

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M
<b>TOLERANCES UNLESS OTHERWISE SPECIFIED</b>
<b>FRACTIONAL</b>
1/16 = ± 1/32
1/32 = ± 1/64

COPYRIGHT © 2013 ALL RIGHTS RESERVED	<b>ACUDOR PRODUCTS</b> Available at <a href="http://www.Hallmann-Sales.com">www.Hallmann-Sales.com</a>			
	6' LADDER – WALL MOUNTED ALUMINUM			
DWN. BY: C.S.	SCALE: 1=12	QUOTE#	DATE: 2/24/10	
CHK. BY:	DWG.#	SHEET SIZE: A	SHEET NO: 1	REV: 1 OF 1